



CE

# CERTIFICATE

## of conformity of the factory production control

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### OPSINOX EW, OPSINOX DW

#### Single and insulated double walled metal chimneys

as registered by BCCA by means of a regularly validated product list reflecting the scope of the FPC-system and placed on the market under the name or trade mark of

**Pronox nv**  
**Venecoweg 22, BE - 9810 Nazareth,**

and produced in the manufacturing plant

**Pronox nv**  
**Venecoweg 22, BE - 9810 Nazareth,**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 1856-1:2009**

under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on 26-10-2015 and will remain valid until 13-12-2023 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

**N° certificate 0749-CPR-BC2-604-17571-EN 1856-1/001-17571 | Valid from 14-12-2018 until 13-12-2023**

Issued in Brussels, on 14 December 2018.

ir. B. De Blaere,  
General Manager

The validity of this certificate can be checked on the website [www.bcca.be](http://www.bcca.be).

BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION NPO  
FOUNDERS: BBRI AND SECO  
RUE D'ARLON 53, BE - 1040 BRUSSELS  
TEL. + 32 2 238 24 11  
MAIL@BCCA.BE | WWW.BCCA.BE

CE  
0749

B  
E  
L  
A  
C  
021 PROD

## Validated scope of the certified FPC-system

**Related to the CE-Certificate of conformity of the factory production control  
0749-CPR-BC2-604-17571-EN 1856-1/001-17571,  
issued on 14 December 2018.**

to Pronox nv in its manufacturing plant Pronox nv, Venecoweg 22, BE - 9810 Nazareth, ,

for single and insulated double walled metal chimneys according to EN 1856-1:2009.

Version of the present document: 4, Date: 14 December 2018.

Product list		
<b>OPSINOX EW4</b>		
Single-wall un-insulated metal flue gas discharge pipes for a negative pressure / atmospheric chimney system.		
Diameter from 111 mm to 400 mm.		
<u>Flue gas discharge pipes</u> T450-N1-D-Vm-L20040-O(200) T450-N1-D-Vm-L20080-O(200)	Diam 111 to 200 Diam 150 to 400	Material: '20' - 1.4301 in accordance with EN 10088 Material: '20' - 1.4301 in accordance with EN 10088
<b>OPSINOX EW6</b>		
Single-wall un-insulated metal flue gas discharge pipes for a negative pressure / atmospheric chimney system.		
Diameter from 111 mm to 400 mm.		
<u>Flue gas discharge pipes</u> T450-N1-W-Vm-L50060-O(200) T450-N1-W-Vm-L50080-O(200)	Diam 111 to 350 Diam 350 to 400	Material: '50' - 1.4404 in accordance with EN 10088 Material: '50' - 1.4404 in accordance with EN 10088
<b>OPSINOX EWP1</b>		
Single-wall un-insulated metal flue gas discharge pipes for a positive pressure chimney system.		
<u>Flue gas discharge pipes</u> T200-P1-W-Vm-L50050-O(50)	Diam 111 to 400	Material: '50' - 1.4404 in accordance with EN 10088



## Validated scope of the certified FPC-system

**Related to the CE-Certificate of conformity of the factory production control  
0749-CPR-BC2-604-17571-EN 1856-1/001-17571,  
issued on 14 December 2018.**

### OPSINOX DW 4 4

Double walled insulated metal flue gas discharge pipes  
for a negative pressure / atmospheric chimney system.

Flue gas discharge pipes  
T450-N1-W-Vm-L50040-O(60)  
T600-N1-W-Vm-L50040-G(80)

Diam 125 to 300

Material: '50' - 1.4404 in accordance with EN  
10088

### OPSINOX DW 6 4

Double walled insulated metal flue gas discharge pipes  
for a negative pressure / atmospheric chimney system.

Flue gas discharge pipes  
T450-N1-W-V3-L50060-O(60)  
T600-N1-W-V3-L50060-G(80)

Diam 125 to 300

Material: '50' - 1.4404 in accordance with EN 10088

### OPSINOX DW i4 i4

Double walled insulated metal flue gas discharge pipes  
for a negative pressure / atmospheric chimney system.

Flue gas discharge pipes  
T450-N1-W-Vm-L20040-O(60)  
T600-N1-W-Vm-L20040-G(80)

Diam 125 to 300

Material: '20' - 1.4301 in accordance with EN 10088

### OPSINOX DW i6G

Double walled insulated metal flue gas discharge pipes  
for a negative pressure / atmospheric chimney system.

Flue gas discharge pipes  
T450-N1-W-Vm-L50040-O(60)  
T600-N1-W-Vm-L50040-G(80)

Diam 125 to 300

Material: '50' - 1.4404 in accordance with EN 10088

---

## Validated scope of the certified FPC-system

---

**Related to the CE-Certificate of conformity of the factory production control  
0749-CPR-BC2-604-17571-EN 1856-1/001-17571,  
issued on 14 December 2018.**

<b>OPSINOX DW i4G</b>		
Double walled insulated metal flue gas discharge pipes for a negative pressure / atmospheric chimney system.		
<u>Flue gas discharge pipes</u> T450-N1-W-Vm-L20040-O(60) T600-N1-W-Vm-L20040-G(80)	Diam 125 to 300	Material: '20' - 1.4301 in accordance with EN 10088
<b>OPSINOX DWP1</b>		
Double walled insulated metal flue gas discharge pipes for a positive pressure chimney system.		
<u>Flue gas discharge pipes</u> T200-P1-W-Vm-L50040-G(20)	Diam 125 to 300	Material: '50' - 1.4404 in accordance with EN 10088

The present document only remains valid as long as the CE-certificate is valid.  
The latest version is made available on BCCA's website.

Issued in Brussels, on 14 December 2018.



ir. B. De Blaere,  
General Manager

